

GEON® Rigid M3005

GEON Performance Solutions - Rigid Polyvinyl Chloride

Thursday, November 2, 2023

General Information

General			
Material Status	• Commercial: Active		
Availability	• Africa & Middle East • Asia Pacific	• Europe • Latin America	• North America
Features	• Low Smoke Emission		
Agency Ratings	• NSF STD-14	• NSF Type I	
Forms	• Pellets		

ASTM & ISO Properties ¹

Physical	Nominal Value (English)	Nominal Value (SI)	Test Method
Density / Specific Gravity	1.40	1.40	ASTM D792
Spiral Flow	24.0 in	61.0 cm	
Molding Shrinkage - Flow	2.0E-3 to 5.0E-3 in/in	0.20 to 0.50 %	ASTM D955
PVC Cell Classification	11432	11432	ASTM D1784
Mechanical	Nominal Value (English)	Nominal Value (SI)	Test Method
Tensile Modulus ²	450000 psi	3100 MPa	ASTM D638
Tensile Strength ² (Yield)	7400 psi	51.0 MPa	ASTM D638
Flexural Modulus	450000 psi	3100 MPa	ASTM D790
Flexural Strength	13300 psi	91.7 MPa	ASTM D790
Impact	Nominal Value (English)	Nominal Value (SI)	Test Method
Notched Izod Impact - Across Flow			ASTM D256A
73°F (23°C), 0.125 in (3.18 mm), Compression Molded	1.0 ft-lb/in	53 J/m	
73°F (23°C), 0.250 in (6.35 mm), Compression Molded	0.70 ft-lb/in	37 J/m	
Hardness	Nominal Value (English)	Nominal Value (SI)	Test Method
Durometer Hardness (Shore D, 10 sec)	82	82	ASTM D2240
Thermal	Nominal Value (English)	Nominal Value (SI)	Test Method
Deflection Temperature Under Load			ASTM D648
66 psi (0.45 MPa), Unannealed, 0.250 in (6.35 mm)	163 °F	72.8 °C	
264 psi (1.8 MPa), Unannealed, 0.250 in (6.35 mm)	162 °F	72.2 °C	
Flammability	Nominal Value (English)	Nominal Value (SI)	Test Method
Flame Rating (0.06 in (1.5 mm), ALL)	V-0	V-0	UL 94

Processing Information

Injection	Nominal Value (English)	Nominal Value (SI)
Processing (Melt) Temp	380 to 395 °F	193 to 202 °C

Notes

¹ Typical properties: these are not to be construed as specifications.

² Type I, 2.0 in/min (51 mm/min)

IMPORTANT: The information contained herein is believed to be accurate, but this information should not be construed as a product specification. It is offered for your consideration, investigation, testing, and verification. The information is based on laboratory work with small-scale equipment and does not necessarily indicate end-product performance. Due to variations in methods, conditions, and equipment used commercially to process this product, no warranties or guarantees are made as to the suitability of this product for any particular application. Full-scale testing and end product performance are the responsibility of the user. GEON Performance Solutions is not liable for and the user assumes all risk and liability of any use or handling of this product. GEON PERFORMANCE SOLUTIONS MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Nothing contained herein is to be considered as permission, recommendation, nor as an inducement to practice any patented invention without permission of the patent owner.